


Specification Sheet

Part Number: MB2.5A10M4



Adhesive Base, .63" x .63", .10" Max Tie Width, .11" Hole Dia, PA66/SR T50, White, 1000/pkg

Article Number

151-00298

Type

MB2.5A

Color

White (WH)

Features & Benefits

- For use with 18 pound cable ties to provide stability when securing bundles.
- Secures with rubber based adhesive backing and/or two or four screws.
- 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

Quantity Per

bag

Product Description

HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

Short Description	Adhesive Base, .63" x .63", .10" Max Tie Width, .11" Hole Dia, PA66/SR T50, White, 1000/pkg
Global Part Name	MB2.5A-PA66-WH
Length L (Imperial)	0.625
Length L (Metric)	15.9
Fixation Method	Screw Mounting and Adhesive
Width W (Imperial)	0.625
Width W (Metric)	15.9
Cable Ties	T18
Height H (Imperial)	.16
Height H (Metric)	4.10
Cable Tie Width Max (Imperial)	0.1
Cable Tie Width Max (Metric)	2.54
Mounting Hole Diameter D (Imperial)	0.11
Mounting Hole Diameter D (Metric)	2.8 mm
Mounting Hole Diameter D Max (Metric)	2.8

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Adhesive	Synthetic rubber with base of polyethylene foam
Flammability	UL 94 V2 (excluding adhesive)
Adhesive Operating Temperature	-4°F to +122°F (-20°C to +50°C)
Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
ROHS Complaint	Yes
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3926909987