

JACKPAC JPTA100MS 24VDC PNP M12

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



Timing relays are used in automation engineering in order to compensate for malfunctions caused by high clock rates.

Short pulses are extended and hence are reliably identified by downstream control components.

Various timing functions such as make and break delays, clock generator and star/delta switchover are available to users.

General ordering data

Order No.	8836630000
Type	JPTA100MS 24VDC PNP M12
Version	JACKPAC, Relays, No. of contacts: 1, NO contact, Rated control voltage: 18...24...30 V DC, Continuous current: 0.4 A, M12 plug/socket, A-coded
GTIN (EAN)	4032248544264
Qty.	1 pc(s).

**JACKPAC
JPTA100MS 24VDC PNP M12**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data
Ratings

Conductor connection system	M12 plug/socket, A-coded	Ambient temperature	0 °C...+55 °C
-----------------------------	--------------------------	---------------------	---------------

Dimensions and weights

Width	36 mm	Height	14.4 mm
Depth	83 mm	Net weight	55 g

Temperatures

Operating temperature	0 °C...+60 °C	Ambient temperature	0 °C...+55 °C
Storage temperature	-20 °C...+85 °C		

Input

Rated control voltage	18...24...30 V DC	Rated current DC	3,5...7,0...10,0 mA
Min. pulse duration	1 ms	Impulse generator input	50 ms

Output

Max. switching voltage, DC	30 V	Continuous current	0.4 A
Switch-off delay	100 ms	Max. switching current	400 mA

Contact specifications

No. of contacts	1	Contact design	NO contact
-----------------	---	----------------	------------

Insulation coordination

Rated voltage	32 V	Impulse withstand voltage	330 V
Protection degree	IP 30 // terminals IP 20	Pollution severity	2
Surge voltage category	I		

Other technical data

Version	Timing relay
---------	--------------

Classifications

ETIM 2.0	EC001439	ETIM 3.0	EC001439
UNSPSC	30-21-19-17	eClass 4.1	39-12-15-19
eClass 5.1	27-14-23-10	eClass 6.0	27-14-23-10
eClass 7.0	27-14-23-10		

Approvals

Approvals



Data sheet...

JACKPAC
JPTA100MS 24VDC PNP M12

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Downloads

Declaration of Conformity [K270_06_06.pdf](#)

[3-D model](#)

**JACKPAC
JPTA100MS 24VDC PNP M12**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Electric symbol

