

## RJ45 bending protection sleeve - VS-08-KS-H/GY - 1654743

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



RJ45 bend protection sleeve, for pin inserts VS-08-ST-H11-RJ45 and VS-08-ST-H21-RJ45, for cable cross section up to 7 mm, color: gray



**Ethernet**

### Key commercial data

Packing unit	1 PCE
Minimum order quantity	5 PCE
GTIN	 4 017918 977801
Custom tariff number	39269097
Country of origin	CHINA

### Technical data

#### Mechanical characteristics

External cable diameter	7 mm
Color	gray
Ambient temperature (operation)	-40 °C ... 80 °C

#### Material data

Inflammability class according to UL 94	V0
Housing material	PA
Degree of protection	IP20

### Classifications

#### ETIM

ETIM 2.0	EC000307
ETIM 3.0	EC001680

# RJ45 bending protection sleeve - VS-08-KS-H/GY - 1654743

## Classifications

### ETIM

ETIM 4.0	EC001680
ETIM 5.0	EC001680

### UNSPSC

UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501
UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501

### eCl@ss

eCl@ss 4.0	27140906
eCl@ss 4.1	27140906
eCl@ss 5.0	27140915
eCl@ss 5.1	27140915
eCl@ss 6.0	27140915
eCl@ss 7.0	27439224

## Accessories

### Accessories

RJ45 male insert - VS-08-ST-H11-RJ45 - 1652716



RJ45 pin insert, CAT5e, 8-pos., shielded, IDC connection method, for litz wires AWG 27 ... 26, with strain relief

RJ45 male insert - VS-08-ST-H21-RJ45 - 1652729



RJ45 male insert, CAT6, 8-pos., shielded, IDC displacement connection, for litz wire AWG 25 ... 24 and solid wires AWG 24, with strain relief

## Drawings

## RJ45 bending protection sleeve - VS-08-KS-H/GY - 1654743

Dimensioned  
drawing

RJ45  
bending  
protection  
sleeve

---

© Phoenix Contact 2013 - all rights reserved  
<http://www.phoenixcontact.com>