



型番	スタッド	H* ±0.2φ	マキソク
C-170737-1	8MM	8.6	38-8
C-170737-2	10MM	10.7	38-10
C-170737-3	2MM	13.2	38-12

DIMENSIONS IN MM DO NOT SCALE PRINT

G	REVISED (P-DWG RET-A)	S.O	3/17/70
F	REVISED (P-DWG REV. A)	T.K	4/1/70
E	REVISED (P-DWG REV. D)	Y.I	3/11/70
D	REVISED (P-DWG REV. A)	J.A	11/23/70
C	ADD JIS マソ (REV. A)	K.K	3/24/70
B	REVISED (P-DWG REV. A)	K.K R.S	10/21/70
A	DELETES MARK * (P-DWG REV. D)	K.K	4/1/70
0	RELEASED (REV. 0)	K.K	3/4/70
4	REVISION RECORD	DR	OK
CR.	K. Kobayashi 3/17/70		
C	Production 3/17/70 Hitachi 3/20/70		

G1. DELETE MARK @ JSA-T160 J.J 4/3/70

1970 JSA USA, INC. ALL RIGHTS RESERVED. AMP PRODUCTS COVERED BY PATENTS AND/OR PATENT PENDING.

MATERIAL: 電気銅

FINISH: 丸孔, 錫めっき

WIRE RANGE: 26-22 AWG 2

INSULATION DIA.:

TRADE MARK:

TOKYO, JAPAN

CLASS:

TYPE: ヴィストランド

TOLERANCE: ±0.1 EXCEPT AS NOTED

SCALE: 2-1

LOC: J A

REV: C-170737 G1

NAME: 丸型端子